



WD LQ003 CEMENT LIQUID MEMBRANE



W威盾

Description:

Weidun®LQ 003 Cement Liquid Membrane is a safe and environment-friendly, highly costeffective liquid product widely used to prevent indoor leakage and moisture.

Uses:

Weidun®LQ 003 Cement Liquid Membrane is designed for areas that need to be waterproofed such as toilet, bathroom, pond, roof and etc.

Advantages:

- Excellent waterproofing and Immersion;
- Weather resistant and high elongation;
- Environmental friendly;
- Ease of apply;

Product Application:



Storage and Handing:

To prevent damage, store liquid emulsion and cement in a clean, dry location, covering as necessary to protect from environment damage. Monitor environmental conditions during storage, handling, and application.





Product Specifications:

| Bucket Size* | 25.0L | |
|--------------------|---------|--|
| Bucket Height | 34.0cm | |
| Bucket Diameter | 27.0cm | |
| Bucket Weight | 20 kg | |
| Full Pallet Weight | 1.2 ton | |

Note: Weidun provide tailored design solutions for bucket size to meet your specific needs, please contact your sales representative for support.

Technical Data Sheet:

| Property | | Standard Minimum Value | Weldun Value |
|--|--|---------------------------|--------------|
| Solid content (%) | | 70 | 72 |
| Tensile strength | No treatment (Mpa) | 1.2 | 1.3 |
| | Heat treatment retention rate (%) | 80 | 86 |
| | Immersion treatment retention rate (%) | 60 | 68 |
| Elongation at break (%) | No treatment | 200 | 225 |
| | Heat treatment | 150 | 167 |
| | Immersion treatment | 150 | 158 |
| Adhesive strength (Mpa) | No treatment | N/A | 0.6 |
| | Heat treatment | N/A | 0.8 |
| | Immersion treatment | N/A | 0.7 |
| Low-temperature flexibility, at -10 °C | | No crack | No crack |

